

This discussion paper is/has been under review for the journal Hydrology and Earth System Sciences (HESS). Please refer to the corresponding final paper in HESS if available.

Balancing energy and environmental concerns: the case of the Kayraktepe dam, Turkey

Ö. Sever¹, Ş. Tiğrek², and N. Şarlak³

¹Prosem Engineering Architectural Consultation, Ankara, Turkey

²Department of Civil Engineering, Middle East Technical University, Ankara, Turkey

³Department of Civil Engineering, University of Gaziantep, Gaziantep, Turkey

Received: 17 September 2012 – Accepted: 25 September 2012 – Published: 16 October 2012

Correspondence to: N. Şarlak (sarlak@gantep.edu.tr)

Published by Copernicus Publications on behalf of the European Geosciences Union.

11769

Abstract

In this study, an alternative solution for a large dam, namely the Kayraktepe Dam in Turkey, is investigated. The dam was planned for flood control, energy generation and flow regulation for a downstream irrigation project more than 30 yr ago, but until now
5 the project has not begun due to it receiving severe criticism about environmental and social considerations. The project formulation was redeveloped several times in the past but the options were not found to be feasible. In this study, a detailed analysis of the available feasibility studies is provided and then a new formulation, consisting of the proposed one medium dam and five run-of-river type hydropower stations instead of a
10 large scale dam, is evaluated. The new formulation is equivalent to the existing project in terms of energy production and flood control. On the other hand, there are some benefits relative to other configurations as solutions to some of the environmental and social problems being addressed.

1 Introduction

15 The idea of building a dam on the Göksu River was proposed more than 30 yr ago. After severe flooding along the river, the Kayraktepe project was designed to control floods, to produce energy and to supply irrigation water in 1982, as a 125 m high large dam. Four different dam locations were studied and finally a rock-fill dam with vertical clay core was chosen as an optimum (Hayashi, 1982). Thenceforth, an international competitive bidding process was initiated and the project was awarded. The World Bank
20 provided loan guarantees of around two hundred million dollars. After the World Bank, Japanese, European and Arab Commercial Banks also provided loans amounting to three hundred fifty million dollars. The implementation of the projects under the investment program was started in 1986, however the World Bank decided not to support the project further after due considerations. The limited funds supplied by the World Bank
25 was used for preliminary works such as camp facilities and access roads. In general,

11770

- Lu, X. X. and Siew, R. Y.: Water discharge and sediment flux changes over the past decades in the Lower Mekong River: possible impacts of the Chinese dams, *Hydrol. Earth Syst. Sci.*, 10, 181–195, doi:10.5194/hess-10-181-2006, 2006.
- MENR (Ministry of Energy and Natural Resources of Turkey): The Procedures and principles of signing water use right agreement for production activities in electricity market, published in Official Newspaper, No: 25150, 26 June 2003, 2003.
- O'Reilly, C. and Silberblatt, R.: Reservoir management in Mediterranean climates through the European water framework directive, *Water Resources Center Archives, Hydrology, University of California*, 2009.
- Öztürk, A.: Sustainability assessment of a hydropower project: A case study of Kayraktepe Dam and HEPP, M.Sc. Thesis, Dept. of Civil Engineering, Hydromechanics Laboratory, Middle East Technical University, Ankara, Turkey, 2011.
- Palmierie, A., Shah, F., and Dinar, A.: Economics of reservoir sedimentation and sustainable management of dams, *J. Environ. Manage.*, 61, 149–163, 2001.
- Poulos, S. E. and Collins, M. B.: Fluvial sediment fluxes to the Mediterranean Sea: a quantitative approach and the influence of dams, *Geological Society, London, Special Publications*, 191, 227–245, 2002.
- Şarlak, N.: Flood frequency estimator with nonparametric approaches in Turkey, *Fresen. Environ. Bull.*, 21, 1083–1089, 2012.
- Scheumann, W., Baumann, V., Mueller, A. L., Mutschler, D., Steiner, S., and Walenta, T.: Environmental impact assessment in Turkish dam planning, *Turkey's water policy: national frameworks and international cooperation*, Springer-Verlag, Berlin Heidelberg, doi:10.1007/978-3-642-1936-2, 2011.
- Sever, Ö.: Kayraktepe dam and HEPP, environmentally acceptable alternative solution, M.Sc. Thesis, Dept. of Civil Engineering, Hydromechanics Laboratory, Middle East Technical University, Ankara, Turkey, 2010.
- Tiğrek, Ş. and Aras, T.: Reservoir Sediment Management, CRC Press/Balkema, Leiden, The Netherlands, 2011.
- Tiğrek, Ş. and Kibaroglu, A.: Strategic role of water resources for Turkey, *Turkey's water policy national frameworks and international cooperation*, Springer-Verlag, Berlin Heidelberg, 27–42, 2011.
- Tiğrek, Ş., Göbelez, Ö., and Aras, T.: Technological Perspectives for Rational Use of Water Resources in the Mediterranean Region (Sustainable management of reservoirs and

11781

- preserving water quality), Bari, Italy, IAM Bari: CIHEM (Centre International de Hautes Etudes Agronomiques Mediterraneenes), *Seria A Semnaires Mediterraneenes*, edited by: El Moujabber, M., Mandi, L., Liuzzi, G. T., Martin, I. I., Rabi, A., and Rodriguez, R., No: 88, Options, ISSN: 1016-121X-ISBN: 2-8352-425-6, 2009.
- WCD: Dams and development, a new framework for decision making, The report of the World Commission on Dams, Eartscan Publications Ltd, London and Sterling, November 16, ISBN: 1-85383-798-9 Paperback and 1-85383-797-0 hardback or available at: www.dams.org, 2000.
- Wildi, W.: Environmental hazards of dams and reservoirs, *Near Curriculum in Natural Environmental Science*, 88, 187–197, 2010.

11782

Table 1. Chronology of critical stages of Kayraktepe HEPP projects.

Date	Event
1936	General Directorate of Electrical Power Resources Survey and Development Administration (EİE) was founded to investigate issues on how rivers in the country could be utilised for energy production.
1953	Initial investigation in the basin was started; Stream Gauging Stations were installed.
1954	State Hydraulic Works (DSİ) was established. The basin scale studies for 26 hydrological basins have been started.
1971	Ramsar Convention or the convention of wetlands was accepted on 3 February 1971.
1977	The Kayraktepe Dam and HEPP project was identified by EİE. The contract awarded to the consortium of EPDC, Su-İş, Su-Yapı and TMB.
1979	Construction of Gezende Dam on the Ermenek Creek was started.
1982	The feasibility report of Kayraktepe Dam and HEPP project released.
1986	The construction of Kayraktepe Dam was awarded by DSİ to EPDC under finance from the World Bank. Small preliminary works done.
1990	Construction of Gezende Dam was completed.
1994	The Göksu Delta was recognised as Ramsar site as Turkey ratified the Convention.
1997	Kayraktepe Dam and HEPP Project was revised.
2000	The World Commission on Dams published an infamous report as "Dams and Development".
2001	Act No: 4628 released: Aims to form a stable, transparent and competitive electricity market to generate sufficient, sustainable and cheaper electricity.
2002	Construction of Ermenek Dam was started.
2003	Regulation for increasing involvement of private sector in the electricity market was established.
2004	Six on-going HEPP developments were transferred to private sector.
2005	Act No: 5346 released: Aims to increase electricity generation from renewable sources.
2006	The construction of Blue Tunnel was started (water transmission from the Göksu River to Konya Plain).
2008	Kayraktepe Dam and HEPP were awarded to a private company. The company, namely BM holding decided to revise the project in order to eliminate environmental effects.
2009	Construction of Ermenek Dam was completed.
2011	Negotiations with DSİ for the new formulation of Kayraktepe Dam and HEPP project were settled. This project was rejected. Although this formulation is enough capable to prevent flood as well as economical and sensitive for both environment and social, the DSİ insisted on large scale dam formulation.
2012	The project revision was restarted according to large scale dam formulation.

11783

Table 2. Salient features of Kayraktepe-2010 formulation.

	Kayraktepe I Diversion weir and HEPP	Kayraktepe II Diversion weir and HEPP	Kayraktepe III Diversion weir and HEPP	Kurtsuyu Diversion weir and HEPP	Kayraktepe Dam and HEPP	Kayraktepe IV Diversion weir and HEPP
Location	Göksu River and Ermenek Creek	Göksu River	Göksu River	Kurtsuyu Creek	Göksu River	Göksu River
Type of weir	RCC	RCC	RCC	RCC	–	RCC
Thalweg Elevation (m)	117.00	106.00	95.50	115.00	41.50	27.00
Operating Elevation (m)	120.00	110.00	104.00	120.00	85.00	37.00
Flood Level (m)	–	–	–	–	93.00	–
Dam Crest Elevation (m)	–	–	–	–	94.50	–
Tailwater Elevation (m)	110.00	104.00	85.00	85.00	37.00	28.30
Design Discharge (m ³ s)	227.00	232.00	237.00	8.00	369.22	369.30
Installed Power (MW)	20.53	12.53	36.53	2.48	152.13	29.35
Energy Production (GWh)	58.80	39.37	114.40	9.68	308.58	57.40
Length of Canal (m)	–	–	5 925.00	2 285.00	–	–
Length of Tunnel (m)	–	–	513.95	–	–	–
Type of spillway	uncontrolled spillway	uncontrolled spillway	uncontrolled spillway	uncontrolled spillway	controlled spillway	uncontrolled spillway
Head pond	–	–	+	+	–	–

11784

Table 5. The flushing coefficients for both formulations.

	Kayraktepe-2010 Formulation	Kayraktepe-1997 Formulation
C_0 (Mm ³)	174.50	1 726.90
MAR (Mm ³)	3010.55	3010.55
MSY (Mm ³)	1.13	1.13
K_w	$174.50/3010.55 = 0.058$	$1\ 726.90/3010.55 = 0.573$
K_t	$174.50/1.13 = 154.42$	$1\ 726.90/1.13 = 1\ 528$

11787




Fig. 1. The location of the Göksu river system and infrastructural development of Göksu Basin.

11788




Fig. 2. Kayraktepe-2010 formulation.